```
    src="https://cdn.jsdelivr.net/npm/ruby-head-wasm-wasi@0.5.0/dist/browser.script.iife.js"
  ></script>
  <script type="text/ruby">
    require "js"
    document = JS.global[:document]
    button = document.getElementById("button")
    response = document.getElementById("response")
    guess = document.getElementById("guess")
    button.addEventListener("click") do |e|
      real_number = (1..10).to_a.sample
      result_text = "The number was #{real_number}. "
      if guess[:value].to_i == real_number
        result_text << "You were right!!"
      else
        result_text << "You were incorrect"
      end
      response[:innerText] = result_text
    end
  </script>
</head>
<body>
  <p>Pick a number 1 through 10</p>
  <input id="guess" />
  <button id="button">Am I right?</button>
  <div id="response"></div>
</body>
</html>
```

In this script, the HTML at the end has a button, a text field, and a placeholder for a response. In the script, after we require a module called js, we then have access to the JavaScript document object as JS.global[:document]. From there, we can use the DOM method getElementById to retrieve DOM elements and access their values as though in a hash (not as attributes). We can even call methods on them, as in addEventListener.

It all adds up to a button that causes a random number to be generated and compared to the value in a text field.

You don't have to do this in the HTML script, you can grab the NPM package directly and evaluate Ruby code, but you have to pass the Ruby code as a string. This is a little clunky right now, but you can see an example at https://github.com/ruby/ruby.wasm/blob/main/packages/npm-packages/ruby-wasm-wasi/example/index.node.js.

This is a very new project as we write this, and we look forward to further developments on the coding experience here.

What's Next

We've covered many different ways Ruby interacts with the web. We've seen Ruby's own utilities, the Rack framework for interactions between web servers and application frameworks, and the Sinatra framework for building basic web applications. Next we look at Ruby style.