```
1    Style/StringLiteralsInterpolation
--
108  Total
```

Most of these issues are that RuboCop's default, for some reason, prefers single-quoted strings. Most of the rest of these are other differences of opinion between the gem author and RuboCop's defaults. (To be honest, the RequiredRubyVersion and MutableConstant cops are probably worth fixing.)

Anyway, at this point we have a couple of options for what we can do with RuboCop just from the command line. As with many other command-line programs, we can pass directory names, file names, or file name patterns to the CLI to limit RuboCop to the listed files: `rubocop lib`, for example.

We can auto-correct all the correctable cops. This will change all the double-quoted strings to single-quoted strings and various and sundry other things that RuboCop is currently complaining about.

To do that, we'd use the `-a` option: `rubocop -a`, and RuboCop will apply auto-correct logic for all the issues it identified. In this case, it would replace all double-quoted strings with single-quoted strings. We don't want to do that right now, but the auto-correct is a quick way to fix many simple RuboCop issues. RuboCop is generally cautious about what it chooses to autocorrect, and most of the corrections are simple, but "cautious" does not mean "perfect," and "most of" does not mean "all," so when you do auto-correct, you want to check the result to make sure the new code is functionally equivalent to the old code.

On the other hand, we could decide that the codebase is so gnarly that we don't want to fix old issues; we just want to start fresh and not create new issues. RuboCop allows us to create a to-do list of existing issues that are excluded from being flagged by future runs with this:

```
$ rubocop --auto-gen-config
```

This will produce a lot of output and in the end it will create a minimal `.rubocop.yml` configuration file and a `.rubocop_todo.yml` file. The `.rubocop_todo.yml` is an extension of the RuboCop configuration that excludes files where existing issues have been found so that RuboCop will ignore them in the future. After running the auto-configuration, we get this:

```
$ rubocop
# A LOT OF OUTPUT ABOUT SPECIFIC COPS AND OUR CONFIGURATION BEING TOO MINIMAL

Inspecting 14 files
..............

14 files inspected, no offenses detected
```

To be clear, the offenses are still there, they are just being suppressed by the todo file.

Configuring RuboCop

Almost everything in RuboCop can be configured, and the file in which to make these changes is `.rubocop.yml`. Here's a sample configuration that clears most of the issues RuboCop identified in our earlier code example:

ruby_style/aaagmnr/.rubocop.yml

```
#inherit_from: .rubocop_todo.yml

AllCops:
```