```
  TargetRubyVersion: 3.2
  NewCops: enable
  SuggestExtensions: false
  Exclude:
    - "bin/**/*"

Metrics/MethodLength:
  Enabled: false

Style/AccessModifierDeclarations:
  EnforcedStyle: inline

Style/Documentation:
  Enabled: false

Style/FrozenStringLiteralComment:
  Enabled: false

Style/StringLiterals:
  EnforcedStyle: double_quotes

Style/StringLiteralsInInterpolation:
  EnforcedStyle: double_quotes

Style/WordArray:
  MinSize: 3
```

At the top, we commented out the line inherit_from: .rubocop_todo.yml. That line was generated in the previous section when we ran the --auto-gen-config command. In general, RuboCop lets you inherit from other configurations so as to modularize the configuration. If we wanted to include separate projects like RuboCop's Rails or RSpec cops, we'd use inherit_from: to include them. The inherit_from mechanism is often used for an organization to specify a common set of standards, and then individual projects use their own configurations to extend or override those standards.

Below that is a section in which we set default values by using the AllCops name. In this case, we're telling RuboCop to treat the code as though it was being written for Ruby 3.2 and to exclude any file in the bin directory. We're also explicitly opting in to new cops and telling RuboCop not to suggest extensions on the grounds that if we don't, RuboCop complains about both of those things in the output every time we run the command.

The settings for individual cops can be changed directly, as this configuration does. We don't need RuboCop to tell us about method length—we trust our team to only have long methods when necessary—so we set Enabled: false for that cop. Any cop can have its Enabled setting set to true or false. Most cops default to true.

If you look at the .rubocop_todo.yml file, notice that every cop also has an Exclude setting that takes a list of files or file patterns that should not have that cop applied. This is helpful in transitioning a codebase to RuboCop because it allows you to be judicious in switching individual files, but in general, you wouldn't use it in your main configuration.

Some cops have their own parameters to set—we set the Style/StringLiterals cop to double_quotes. We still want this cop to work, we just want it to accept double quotes as the ideal and flag single quotes. Similarly, the Style/WordArray cop, which wants us to change all our ["cat", "dog"] tests to the word array syntax of %w[cat dog], has a parameter that sets the minimum size of the array that it cares about. We don't really mind the array syntax for two-element arrays, so we set the minimum value to 3.