```
"Greek pi: \u{3c0}"         # => "Greek pi: π"
"Greek \u{70 69 3a 20 3c0}" # => "Greek pi: π"
```

Literals containing \u will always be encoded UTF-8, regardless of the source file encoding.

The bytes method is a convenient way to inspect the bytes in a string object. Notice that in the following code, the 16-bit codepoint is converted to a two-byte UTF-8 encoding:

```
# encoding: utf-8
"pi: \u03c0".bytes  # => [112, 105, 58, 32, 207, 128]
```

Unicode in Syntax

Ruby allows you to use Unicode characters as variable and method names

```
def ∑(*args)
  args.inject(:+)
end

puts ∑(1, 3, 5, 9)
```

produces:

```
18
```

Of course, this way can lead to some pretty obscure and hard-to-use code. (For example, is the summation character in the previous code a real summation, \u2211, or a Greek sigma, \u03a3?) Just because we *can* do something doesn't mean we necessarily *should*….

Ranges

expression .. expression

expression ... expression

Outside the context of a conditional expression, EXPR..EXPR and EXPRESSION...EXPRESSION construct Range objects. The two-dot form is an inclusive range; the one with three dots is a range that excludes its last element.

The elements on either side of the range can be any object that implements a method called succ that returns the next object in the sequence. This includes all numbers and strings. (If the range is only being used for comparison purposes and as a sequence, then the objects only need to implement the <=> comparison operator.)

A range can be constructed without a start value, as in ..5 or without an end value, 5... In these cases the range is an infinite sequence, and while that is potentially useful in theory, in practice, the infinite ranges are often used when taking a subelement of an array, where the infinite side is a stand in for the edge of the array:

```
["a", "b", "c", "d", "e"][..2] # => ["a", "b", "c"]
["a", "b", "c", "d", "e"][2..] # => ["c", "d", "e"]
```

Arrays

[*expression*, *expression*, ...]

Literals of class Array are created by placing a comma-separated series of object references between square brackets. A trailing comma is ignored.