$* → Array	An array of strings containing the command-line options from the invocation of the program. Options used by the Ruby interpreter will have been removed. [r/o]
$" → Array	An array containing the filenames of modules loaded by require. [r/o]
$$ → Fixnum	The process number of the program being executed. [r/o]
$? → Process::Status	The exit status of the last child process to terminate. [r/o, thread]
$: → Array	An array of strings, where each string specifies a directory to be searched for Ruby scripts and binary extensions used by the load and require methods. The initial value is the value of the arguments passed via the -I command-line option, followed by an installation-defined standard library location. This variable may be updated from within a program to alter the default search path; typically, programs use $: << dir to append dir to the path. [r/o]
$-a → Object	True if the -a option is specified on the command line. [r/o]
__callee__ → Symbol	The name of the lexically enclosing method.
$-d → Object	Synonym for $DEBUG.
$DEBUG → Object	Set to true if the -d command-line option is specified.
__ENCODING__ → String	The encoding of the current source file. [r/o]
__FILE__ → String	The name of the current source file. [r/o]
$F → Array	The array that receives the split input line if the -a command-line option is used.
$FILENAME → String	The name of the current input file. Equivalent to $<.filename. [r/o]
$-i → String	If in-place edit mode is enabled (perhaps using the -i command-line option), $-i holds the extension used when creating the backup file. If you set a value into $-i, enables in-place edit mode, as described in the options descriptions on page 235.
$-I → Array	Synonym for $:. [r/o]
$-l → Object	Set to true if the -l option (which enables line-end processing) is present on the command line. See the options description on page 234. [r/o]
__LINE__ → String	The current line number in the source file. [r/o]
$LOAD_PATH → Array	A synonym for $:. [r/o]
$LOADED_FEATURES → Array	Synonym for $". [r/o]
__method__ → Symbol	The name of the lexically enclosing method.
$PROGRAM_NAME → String	Alias for $0.
$-p → Object	Set to true if the -p option (which puts an implicit while gets...end loop around your program) is present on the command line. See the options description on page 234. [r/o]
$SAFE → Fixnum	The current safe level. This variable's value may never be reduced by assignment. [thread]