$VERBOSE → Object	Set to true if the -v, --version, -W, or -w option is specified on the command line. Set to false if no option, or -W1 is given. Set to nil if -W0 was specified. Setting this option to true causes the interpreter and some library routines to report additional information. Setting to nil suppresses all warnings (including the output of Object#warn).
$-v, $-w → Object	Synonyms for $VERBOSE.
$-W → Object	Return the value set by the -W command-line option.

Standard Objects

ARGF → Object	Provides access to a list of files. Used by command line processing. See ARGF, on page 238.
ARGV → Array	A synonym for $*.
ENV → Object	A hash-like object containing the program's environment variables. An instance of class Object, ENV implements the full set of Hash methods. Used to query and set the value of an environment variable, as in ENV["PATH"] and ENV["term"]="ansi".
false → FalseClass	Singleton instance of class FalseClass. [r/o]
nil → NilClass	The singleton instance of class NilClass. The value of uninitialized instance and global variables. [r/o]
self → Object	The receiver (object) of the current method. [r/o]
true → TrueClass	Singleton instance of class TrueClass. [r/o]

Global Constants

DATA → IO	If the main program file contains the directive __END__, then the constant DATA will be initialized so that reading from it will return lines following __END__ from the source file.
FALSE → FalseClass	Constant containing reference to false.
NIL → NilClass	Constant containing reference to nil.
RUBY_COPYRIGHT → String	The interpreter copyright.
RUBY_DESCRIPTION → String	Version number and architecture of the interpreter.
RUBY_ENGINE → String	The name of the Ruby interpreter. Returns "ruby" for Matz's version. Other interpreters include macruby, ironruby, jruby, and rubinius.
RUBY_PATCHLEVEL → String	The patch level of the interpreter.
RUBY_PLATFORM → String	The identifier of the platform running this program. This string is in the same form as the platform identifier used by the GNU configure utility (which is not a coincidence).
RUBY_RELEASE_DATE → String	The date of this release.
RUBY_REVISION → String	The revision of the interpreter.
RUBY_VERSION → String	The version number of the interpreter.
STDERR → IO	The actual standard error stream for the program. The initial value of $stderr.