A return expression immediately exits a method with the value of the expression passed to return.

return ‹*expr*›*

The value of a return is nil if it is called with no parameters, the value of its parameter if it is called with one parameter, or an array containing all of its parameters if it is called with more than one parameter.

A return expression can be used at the top level, outside of a method call, in which case it stops execution of the program and exits Ruby.

super

super ‹ (‹, *param*›* ‹, **array*›) › ‹*block*›

Within the body of a method, a call to super acts like a call to the original method, except that the search for a method body starts in the superclass of the object that contained the original method. Remember that instance methods defined in included modules act as though they are in anonymous superclasses, so a method so defined will be found by a call to super. Similarly, if super is called from a method that has been prepended to the original class, then super starts its search in the original class.

If no parameters (and no parentheses) are passed to super, the original method's parameters will be passed; otherwise, the parameters to super will be passed.

Operator Methods

expr operator
operator expr
expr1 operator expr2

If the operator in an operator expression corresponds to a redefinable method (see Table 13, Ruby operators (high to low precedence), on page 455), Ruby will execute the operator expression as if it had been written like this:

(*expr1*).*operator*() *or*
(*expr1*).*operator*(*expr2*)

Attribute Assignment

receiver.attrname = rvalue

When the form receiver.attrname appears as an lvalue, Ruby invokes a method named attrname= in the receiver, passing rvalue as a single parameter. The value returned by this assignment is always rvalue—the return value of the method is discarded. If you want to access the return value (in the unlikely event that it isn't the rvalue), send an explicit message to the method.

```
class Demo
  attr_reader :attr

  def attr=(val)
    @attr = val
    "return value"
  end
end
```