Format	Meaning
%Z	Time zone name
%+	Date and time, not supported by Time class.

Table 14—Time#strftime directives

Using Time Instances

Once you have a Time instance, you can extract all the various attributes. Every attribute that might get passed in as part of a constructor call has an associated getter method: year, month (aliased as mon), day (aliased as mday), hour, min, sec, subsec. All of these methods return the integer value of that attribute except for subsec, which returns either a Rational or integer zero.

A Time instance includes a few calculated attributes:

- dst? returns true if the time zone is a daylight savings time zone.
- nsec returns the subseconds in nanoseconds.
- usec returns the subseconds in microseconds.
- wday returns the day of the week as an integer with Sunday as 0, Monday as 1, and so on.
- There are also a series of methods called sunday?, monday? and so on that return true if the day of the week matches that day.
- yday returns the integer day of the year, so January 1st is 1, February 12th is 33, and so on.
- zone returns the name of the time zone.

A Time instance can be the left side of an addition operation and have a number added to it. A new time object is returned with the number of seconds added to the time.

```
t = Time.now
t         # => 2023-03-25 18:45:15.871763 -0500
t + 100   # => 2023-03-25 18:46:55.871763 -0500
```

A Time instance can be the left side of a subtraction operation. The right side can be a number, in which case a new instance is returned with the number of seconds subtracted from the time. Alternately, a second Time instance can be the right operand, in which case the result is the number of seconds between the two times as a float:

```
t = Time.now
t         # => 2023-03-25 18:45:15.958188 -0500
t2 = t - 100
t2        # => 2023-03-25 18:43:35.958188 -0500
t - t2    # => 100.0
```

Time implements the <=> operator and includes the Comparible module, so Time instances can be sorted and compared using all the logical comparison operators.

Converting Time

You can convert a Time instance to a number with the methods to_f, to_i, and to_r. These return the number of seconds that have passed since the Unix Epoch date as a float, integer, or rational, respectively.