- Fold the seam allowance along top and bottom edges
- Fold the seam allowance of the square edges on the wrong side and press
- Machine stitch in flat rows on the right side of the belt.

DO YOU KNOW?

Who invented belt?

Belts as suspenders were used as back as 300 years back. Modern belts were first invented in 1820 by Albert Thurston.

9.2.3 Summary for Belts

Belts play an essential role in garments. It is an important fashion accessory worn with garments. There are different types of belt available in the market. Each and every type is designed for a specific purpose. Belts are constructed with numerous materials. Every belt is finished with buckle and eyelets. Bows are sometimes attached for design effect. Belts have its unique applications in its own way. They could be varied according to the pattern, purpose and the type of wearer.

9.3 Bows

Bow is a fashionable accessory used on garments. It is a common trimming found in hats. Bows add beauty and enhancement to the finished garments. These are made of fabric and used with buttons at times. They are usually added to girls and women garments. Wedding gowns, hats and party wear dresses are always designed with bows. Bows create a beautiful girlish look when worn.

9.3.1 Types of Bow

Bows are classified into three types based on the construction. They are as follows;

- Simple Bows
- Gathered Bows
- Ribbon Bows

9.3.1.1 Simple Bows

A simple bow is shaped like a butterfly. Sometimes it looks like a longer flowery bow. The wider the bow, the longer is the length required for tying the bow. Normally, the finished edges are wider than the middle part which is narrower. A wide finished width is required with turnings and neat finishing. This is one of the most attractive types of bow.



Figure 9.15 Simple Bow

Method of Construction

- Cut the fabric in cross grain and Fold the fabric in lengthwise pattern
- Shape as per the design
- Place the fabric right sides together and sew the ends
- Leave 5 cms (2 inches) unstitched at the center
- Trim the seam allowance to 0.6cm, slit corners and press seam lines neatly

XII TDD_English version CHAPTER 09.indd 132 1/13/2020 3:25:47 PM