10.10.3 Steps for Construction of Basic Skirt

- Complete the darts
- Finish the plackets
- Join the side seams
- Attach the waist band
- Fix the fasteners
- Press neatly
- Finish the front opening placket

10.10.4 Steps for Construction of Shirt

- Mark the patterns on to the fabric
- Name the patterns correctly
- Cut front bodice, back bodice, yoke, collar band, main collar and pocket
- Stitch the yoke on the back of the shirt
- Finish the plackets on the front openings
- Attach collar and collar band
- Join shoulder to neck
- Attach collar at neckline
- Attach side seams and finish the bottom of the shirt
- Join the sleeves
- Press neatly

10.10.5 Steps for Construction of Pant

- Mark the pattern on the fabric
- Cut the fabric accordingly
- Join the crotches
- Stitch the fly opening
- Attach the zipper
- Join the side seams and centre seam
- Attach the waist band
- Fix fasteners
- Press neatly

10.11 Sewing Tips

- All the seams need double machining. This helps the stitch not to rip so easily.
- While sewing the shoulder seams, start from the armhole edge to the neck edge, double machine the seam. Make sure that the second stitch does not shift from the seam line.
- All the straight seams should be stitched in a straight line, irregularities will affect the appearance of the garment.
- While attaching the facing, keep the work piece straight.
- While making gathers, set machine on the largest stitch size, loosen the top tension slightly and machine two rows, one on the seam line and one 0.56 centimetre above it. Wind the top threads round a pin and pull up to the desired length by the bobbin thread only. Ease the fabric gently while pulling to avoid breaking the thread.
- While attaching an eased or gathered section of a garment, always keep it on top to ensure evenness and to keep the gathers from shifting.
- While attaching pocket and while stitching down the pleats, double-machine the edges for reinforcement.
- While attaching ruffles or lace, provide extra ease at corners.
- A curved seam is stitched in the same way as plain seam but the edges are notched so that the seams may be pressed flat.

XII TDD_English version CHAPTER 10.indd 163 1/13/2020 3:29:36 PM