c.	Friction by use of the rubbing board	• Washing is carried out in a deep sink. • Place a part of the soiled cloth on the rubbing board and soap well. • Rinse well in warm water.	
II.	Suction washing friction with a suction washer	• A suction washer consists of non-rusting material. • It may be of small size or large size.	
		• Make a permanent lather on the water with soap solution or soap flakes. • Immerse the soiled article in soapy water and repeatedly press suction washer down on the article. • The vacuum formed causes the soapy water drawn through the clothes. • The repeated suction of the soapy water through the clothes cleanses the fabric.	It is a quick and practical method of cleansing large quantities of soiled articles. It can be used on garments of any fabric and colour.
III.	Washing by kneading and squeezing	• Knead and squeeze the soiled fabric in warm soapy water without lifting out of the water. • Very soiled parts should be placed on the palm of the left hand and should be kneaded and squeezed until the dirt is loosened. • Rinse thoroughly to remove all traces of soap.	



Figure 5.14 Scrubbing Board Suction Washer

5.3.1.3 Washing by Machine

A washing machine is a machine designed to clean laundry such as clothing, towels and sheets. Clothing had been hand washed for thousands of years to remove loose dirt, rubbing with soap to remove oils and stains. For particularly dirty clothing covered with mud or dirt, it is necessary to constantly rub and flex the cloth to break apart solids and help the soap penetrate through thick, dry or sticky layers of soil on the cloth.

Washing machine technology was developed to reduce the drudgery of this scrubbing and rubbing process.

XII TDD_English version CHAPTER 05.indd 64 1/13/2020 3:02:05 PM