Kubernetes cluster manually on top of virtual machines. Instead, we'll move up the abstraction staircase and go for a solution managed by the platform. When we use DigitalOcean Kubernetes (https://docs.digitalocean.com/products/kubernetes), the platform will take care of many infrastructural concerns, so that we developers can focus more on application development.

You can straightforwardly create a new Kubernetes cluster using doctl. I promised that we would deploy Polar Bookshop in a real production environment, and that's what we'll do, although I won't ask you to size and configure the cluster as I would in a real scenario.

For starters, setting up a Kubernetes cluster is not a developer's responsibility—it's a job for the platform team. Second, it would require more in-depth coverage of Kubernetes than is provided by this book to fully understand the configuration. Third, I don't want you to incur extra costs on DigitalOcean for using a lot of computational resources and services. Cost optimization is a cloud property that applies to real applications. However, it might become expensive if you're trying things out or running demo applications. Please keep an eye on your DigitalOcean account to monitor when your free trial and $100 credit expire.

Each cloud resource can be created in a data center hosted in a specific geographical region. For better performance, I recommend you choose one near to you. I'll use "Amsterdam 3" (`ams3`), but you can get the complete list of regions with the following command:

```
$ doctl k8s options regions
```

Let's go ahead and initialize a Kubernetes cluster using DigitalOcean Kubernetes (DOKS). It will be composed of three worker nodes, for which you can decide the technical specifications. You can choose between