different options in terms of CPU, memory, and architecture. I'll use nodes with 2 vCPU and 4 GB of memory:

```
$ doctl k8s cluster create polar-cluster \                                  ❶
    --node-pool "name=basicnp;size=s-2vcpu-4gb;count=3;label=type=basic;" \❷
    --region <your_region>                                                  ❸
```

❶ Defines the name of the cluster to create

❷ Provides the requested specifications for the worker nodes

❸ The data center region of your choice, such as "ams3"

NOTE If you'd like to know more about the different compute options and their prices, you can use the `doctl compute size list` command.

The cluster provisioning will take a few minutes. In the end, it will print out the unique ID assigned to the cluster. Take note, since you'll need it later. You can fetch the cluster ID at any time by running the following command (I have filtered the results for the sake of clarity):

```
$ doctl k8s cluster list

ID              Name             Region    Status     Node Pools
<cluster-id>    polar-cluster    ams3      running    basicnp
```

At the end of the cluster provisioning, doctl will also configure the context for your Kubernetes CLI so that you can interact with the cluster running on DigitalOcean from your computer, similar to what you've done so far with your local cluster. You can verify the current context for kubectl by running the following command:

```
$ kubectl config current-context
```

NOTE If you want to change the context, you can run `kubectl config use-context <context-name>`.