previously. Remember that I asked you to take notes of the resource IDs for PostgreSQL and Kubernetes? Use them in the following command to configure the firewall and secure access to the database server:

```
$ doctl databases firewalls append <postgres_id> --rule k8s:<cluster_id>
```

Next, let's create two databases to be used by Catalog Service (`polardb_catalog`) and Order Service (`polardb_order`). Remember to replace `<postgres_id>` with your PostgreSQL resource ID:

```
$ doctl databases db create <postgres_id> polardb_catalog
$ doctl databases db create <postgres_id> polardb_order
```

Finally, let's retrieve the details for connecting to PostgreSQL. Remember to replace `<postgres_id>` with your PostgreSQL resource ID:

```
$ doctl databases connection <postgres_id> --format Host,Port,User,Password

Host          Port          User          Password
<db-host>     <db-port>     <db-user>     <db-password>
```

Before concluding this section, let's create some Secrets in the Kubernetes cluster with the PostgreSQL credentials required by the two applications. In a real-world scenario, we should create dedicated users for the two applications and grant limited privileges. For simplicity, we'll use the admin account for both.

First, create a Secret for Catalog Service using the information returned by the previous `doctl` command:

```
$ kubectl create secret generic polar-postgres-catalog-credentials \
    --from-literal=spring.datasource.url=
➥jdbc:postgresql://<postgres_host>:<postgres_port>/polardb_catalog \
```