auditing data
enabling and configuring JDBC 163 – 165
protecting user data with Spring Security and Spring Data R2DBC 437 – 441
adding audit metadata for users who created or updated R2DBC data entity 438 – 439
defining auditor to capture who created or updated R2DBC data entity 437 – 438
ensuring user data privacy 440 – 441
writing Flyway migration to add new audit metadata to schema 439
testing data auditing and protection with @WithMockUser and Spring Data R2DBC 441 – 443
testing data auditing with Spring Data and @WithMockUser 436 – 437
with Spring Security and Spring Data JDBC 433 – 436
adding audit metadata for users who created or updated JDBC data entity 434 – 435
defining auditor to capture who created or updated JDBC data entity 433 – 434
writing Flyway migration to add new audit metadata to schema 435 – 436
AuditorAware bean 433 – 434
authentication 374 – 382
15-Factor methodology 41 – 42
authenticating users with OpenID Connect 374 – 378
exchanging user information with JWT 378 – 379
registering application in Keycloak 379 – 382
with Spring Security and OpenID Connect 382 – 393
adding new dependencies 383
basic Spring Security configuration 384 – 385
configuring integration between Spring Security and Keycloak 383 – 384
configuring user logout in Spring Security and Keycloak 390 – 393
inspecting authenticated user context 386 – 390
See also *security*
Authentication object 387, 420, 433
authorization
15-Factor methodology 41 – 42
with Spring Cloud Gateway and OAuth2 407 – 417
customizing tokens and propagating user roles 412 – 417
token relay from Spring Cloud Gateway to other services 409 – 412
Authorization Code 376
Authorization Code flow, OAuth2 376
Authorization header 410 – 411, 417 – 418, 427
Authorization Server 374 – 375, 407 – 408
automation 16 – 17
autoscaling.knative.dev/minScale annotation 579
az postgres server create command 149
Azure Kubernetes Service (AKS) 9

B

BaaS (Backend as a Service) model 28
backend-for-frontend pattern 295
backing services 39, 228
Barr, Jeff 20
basedOnPreviousValue parameter 303
bases 506 – 507
{baseUrl} placeholder 391
bearer tokens 412