managing logs with Loki, Fluent Bit, and Grafana 452 – 455
Spring Boot 449 – 451
metrics and monitoring with 464 – 472
configuring metrics with Spring Boot Actuator and Micrometer 465 – 467
configuring Prometheus metrics in Kubernetes 470 – 472
monitoring metrics with Prometheus and Grafana 467 – 470
Polar Bookshop 66
properties of cloud native applications 14 – 15
OCI (Open Container Initiative) 26, 52, 583
Octant 244 – 245, 588
octant command 539
OidcClientInitiatedServerLogoutSuccessHandler class 390, 392
oidcLogoutSuccessHandler() method 392
OIDC (OpenID Connect) 374
OIDC Provider 376
OidcUser class 388, 401, 409, 416
OidcUser type 387, 441
onError() operator 273
onErrorResume() operator 285
OOMKilled (OutOfMemory killed) status 536
Open Container Initiative (OCI) 26, 52, 583
OpenID Connect
authenticating users with 374 – 378
authentication with 382 – 393
adding new dependencies 383
basic Spring Security configuration 384 – 385
configuring integration between Spring Security and Keycloak 383 – 384
configuring user logout in Spring Security and Keycloak 390 – 393
inspecting authenticated user context 386 – 390
testing 400 – 404
testing CSRF (Cross-Site Request Forgery) 402 – 404
testing OIDC authentication 400 – 402
testing authentication 400 – 402
OpenID Connect in Action (Siriwardena) 375
openid scope 413
open state 304 – 305
OpenTelemetry 472 – 479
configuring tracing in Spring Boot with 475 – 479
managing traces with Tempo and Grafana 474 – 475
OpenTelemetry (OTel) 473
OpenTelemetry protocol (OTLP) 477
Operator 596 – 597
optimistic locking 159
Optional<Customer> objects 258
orchestration 27 – 28
Order() constructor 439, 442
order-accepted.dispatcher-service queue 348 – 350
OrderAcceptedEvent message 362
order-accepted exchange 349 – 351
OrderAcceptedMessage object 351