not ready for production. For more information, you can refer to the documentation on GitHub: https://github.com/ThomasVitale/paketo-arm64.

The first time you run the task, it will take a minute to download the packages used by Buildpacks to create the container image. The second time it will take only a few seconds. The resulting image will be named `catalog-service:0.0.1-SNAPSHOT` by default (`<project_name>:<version>`). You can run the following command to get the details of the newly created image:

```
$ docker images catalog-service:0.0.1-SNAPSHOT
REPOSITORY        TAG              IMAGE ID       CREATED        SIZE
catalog-service   0.0.1-SNAPSHOT   f0247a113eff   42 years ago   275MB
```

NOTE You might have noticed in the previous command's output that it looks like the image was created 42 years ago. That's a convention used by Cloud Native Buildpacks to achieve reproducible builds. Subsequent execution of the build command should give the same output if nothing is changed in the input. Using an accurate creation timestamp would make that impossible, so Cloud Native Buildpacks uses a conventional timestamp (January 1, 1980).

The last thing to do is run the image and verify that the containerized application is working correctly. Open a Terminal window and run the following command:

```
$ docker run --rm --name catalog-service -p 8080:8080 \
    catalog-service:0.0.1-SNAPSHOT
```

WARNING If you're running the container on an Apple Silicon computer, the previous command might return a message like "WARNING: The requested image's platform (linux/amd64) does not match the detected host platform (linux/arm64/v8) and no specific platform was requested." In that case, you'll need to include an additional argument to the preceding command (before the image name) until support for ARM64 is added to Paketo Buildpacks: `--platform linux/amd64`.

You can refer to figure 2.8 for a description of the command.