```
package com.polarbookshop.catalogservice.domain;

import java.util.Optional;
import com.polarbookshop.catalogservice.config.DataConfig;
import org.junit.jupiter.api.Test;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.boot.test.autoconfigure.data.jdbc.DataJdbcTest;
import org.springframework.boot.test.autoconfigure.jdbc
➥ .AutoConfigureTestDatabase;
import org.springframework.context.annotation.Import;
import org.springframework.data.jdbc.core.JdbcAggregateTemplate;
import org.springframework.test.context.ActiveProfiles;
import static org.assertj.core.api.Assertions.assertThat;

@DataJdbcTest                                                          ❶
@Import(DataConfig.class)                                              ❷
@AutoConfigureTestDatabase(                                            ❸
  replace = AutoConfigureTestDatabase.Replace.NONE
)
@ActiveProfiles("integration")                                         ❹
class BookRepositoryJdbcTests {

  @Autowired
  private BookRepository bookRepository;

  @Autowired
  private JdbcAggregateTemplate jdbcAggregateTemplate;                 ❺

  @Test
  void findBookByIsbnWhenExisting() {
    var bookIsbn = "1234561237";
    var book = Book.of(bookIsbn, "Title", "Author", 12.90);
    jdbcAggregateTemplate.insert(book);                                ❻
    Optional<Book> actualBook = bookRepository.findByIsbn(bookIsbn);

    assertThat(actualBook).isPresent();
    assertThat(actualBook.get().isbn()).isEqualTo(book.isbn());
  }
}
```

❶ Identifies a test class that focuses on Spring Data JDBC components

❷ Imports the data configuration (needed to enable auditing)

❸ Disables the default behavior of relying on an embedded test database since we want to use Testcontainers

❹ Enables the “integration” profile to load configuration from application-integration.yml

❺ A lower-level object to interact with the database

❻ JdbcAggregateTemplate is used to prepare the data targeted by the test.