A container image can be run with the `docker run` command, which starts a container and executes the process described in the Dockerfile as the entry point:

```
$ docker run --rm my-java-image:1.0.0

openjdk 11.0.15 2022-04-19
OpenJDK Runtime Environment (build 11.0.15+10-Ubuntu-0ubuntu0.22.04.1)
OpenJDK 64-Bit Server VM (build 11.0.15+10-Ubuntu-0ubuntu0.22.04.1, mixed mode)
```

After completing the execution, the container will stop. Since you used the `--rm` argument, the container will be removed automatically after the execution ends.

NOTE When you run the previous command, you'll see that the default OpenJDK in Ubuntu 22.04 is Java 11 instead of the 17 version we are working with throughout the book.

Let's now see how to publish the image to a container registry.

6.1.3 Publishing images on GitHub Container Registry

So far you have learned how to define, build, and run a container image. In this section, I'll complete the picture by expanding on container registries.

A container registry is to images what a Maven repository is to Java libraries. Many cloud providers offer their own registry solutions with extra services, like image scanning for vulnerabilities and certified images. By default, a Docker installation is configured to use the container registry provided by the Docker company (Docker Hub), which hosts images for many popular open source projects, like PostgreSQL, RabbitMQ, and Redis. We'll keep using it to pull images for third parties, as you did for Ubuntu in the previous section.