NOTE If you don't add any network configuration, Docker Compose will automatically create one for you and make all the containers in the file join it. That means they can interact with each other through their container names, relying on Docker's built-in DNS server.

It's good practice to gather all deployment-related scripts in a separate codebase and, possibly, in a separate repository. Go ahead and create a new `polar-deployment` repository on GitHub. It'll contain all the Docker and Kubernetes scripts needed to run the applications composing the Polar Bookshop system. Inside the repository, create a "docker" folder to host the Docker Compose configuration for Polar Bookshop. In the source code accompanying the book, you can refer to Chapter06/06-end/ polar-deployment for the final result.

In the polar-deployment/docker folder, create a docker-compose.yml file, and define the services to run as follows.

Listing 6.7 Docker Compose file describing the catalog services

```
version: "3.8"                                    ❶
services:                                         ❷

  catalog-service:                                ❸
    depends_on:
      - polar-postgres                            ❹
    image: "catalog-service"                      ❺
    container_name: "catalog-service"             ❻
    ports:                                        ❼
      - 9001:9001
    environment:                                  ❽
      - BPL_JVM_THREAD_COUNT=50                   ❾
      - SPRING_DATASOURCE_URL=
➥jdbc:postgresql://polar-postgres:5432/polardb_catalog
      - SPRING_PROFILES_ACTIVE=testdata           ❿

  polar-postgres:
    image: "postgres:14.4"
    container_name: "polar-postgres"
    ports:
      - 5432:5432
```