That's it for this section. You can stop and remove both containers with the following command from the same folder where you keep your docker-compose.yml file:

```
$ docker-compose down
```

NOTE In this book I'm only covering those Docker topics needed in your journey to successfully deploy Spring Boot applications in production with Kubernetes. If you're interested in learning more about Docker images, networks, volumes, security, and architecture, refer to the official documentation on https://docs.docker.com. Also, Manning has a few books in its catalog on the subject, such as *Learn Docker in a Month of Lunches* by Elton Stoneman (Manning, 2020) and *Docker in Practice*, second edition, by Ian Miell and Aidan Hobson Sayers (Manning, 2019).

When you make changes to an application, you don't want to build and publish a new image manually. That's a job for an automated workflow engine like GitHub Actions. The following section will show you how to complete the commit stage of the deployment pipeline we started in chapter 3.

6.4 Deployment pipeline: Package and publish

In chapter 3, we started implementing a deployment pipeline to support continuous delivery for the Polar Bookshop project. Continuous delivery is a holistic engineering approach for quickly, reliably, and safely delivering high-quality software. The deployment pipeline is the primary pattern for automating the entire journey from code commit to releasable software. We identified three main stages for the deployment pipeline: commit stage, acceptance stage, and production stage.

We'll continue focusing on the commit stage. After a developer commits new code to the mainline, this stage goes through build, unit tests,