ReplicaSet (more on this later) and a `template` part describing the specifications for creating the desired Pod and containers.

Listing 7.2 The desired state for the Catalog Service deployment

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: catalog-service
  labels:
    app: catalog-service
spec:
  selector:                                                    ❶
    matchLabels:
      app: catalog-service
  template:                                                    ❷
    metadata:
      labels:                                                  ❸
        app: catalog-service
    spec:
      containers:                                              ❹
      - name: catalog-service                                  ❺
        image: catalog-service                                 ❻
        imagePullPolicy: IfNotPresent                          ❼
        ports:
          - containerPort: 9001                                ❽
        env:                                                   ❾
          - name: BPL_JVM_THREAD_COUNT                         ❿
            value: "50"
          - name: SPRING_DATASOURCE_URL
            value: jdbc:postgresql://polar-postgres/polardb_catalog
          - name: SPRING_PROFILES_ACTIVE
            value: testdata
```

❶ Defines the labels used to select the Pods to be scaled

❷ The template for creating a Pod

❸ Labels attached to the Pod object. They should match the ones used as selectors.

❹ The list of containers in the Pod (one in this case)

❺ The name of the Pod

❻ The image used to run the container. No tag is defined, so “latest” will be used implicitly.

❼ Instructs Kubernetes to pull the image from a container registry only if it’s not present locally yet

❽ The ports exposed by the container