❾ The list of environment variables passed to the Pod

❿ A Paketo Buildpacks environment variable to configure the number of threads for memory calculation

A value for the spring.datasource.url property pointing to the PostgreSQL Pod deployed previously

Enables the “testdata” Spring profile

The `containers` part should look familiar, since it resembles how you defined containers in the `services` section of a Docker Compose file. Like you did with Docker, you can use an environment variable to define the URL for the PostgreSQL instance the application should use. The hostname part of the URL (`polar-postgres`) is the name of the Service object that was used to expose the database and was created previously from the kubernetes/platform/development folder. You’ll learn more about Services later in the chapter. For now, it’s enough to know that `polar-postgres` is the name through which other objects in the cluster can communicate with the PostgreSQL instance.

In a production scenario, the image would be fetched from a container registry. During development, it’s more convenient to work with local images. Let’s build one for Catalog Service, as you learned in the previous chapter.

Open a Terminal window, navigate to the Catalog Service root folder (catalog-service), and build a new container image as follows:

```
$ ./gradlew bootBuildImage
```

TIP If you’re working on ARM64 machines (such as Apple Silicon computers), you can add the `--builder ghcr.io/thomasvitale/java-builder-arm64` argument to the previous command to use an experimental version of Paketo Buildpacks with ARM64 support. Be aware that it’s experimental and not ready for production. For more information, you can refer to the documentation on GitHub: https://github.com/ThomasVitale/paketo-arm64. Without this workaround, until official support is added (https://github.com/paketo-buildpacks/stacks/issues/51), you can still