`deployment` repository, and run the following command to deploy PostgreSQL:

```
$ kubectl apply -f services
```

Let's now see how to configure Tilt to establish that automated development workflow.

Tilt can be configured via a *Tiltfile*, an extensible configuration file written in Starlark (a simplified Python dialect). Go to your Catalog Service project (`catalog-service`) and create a file named "Tiltfile" (with no extension) in the root folder. The file will contain three main configurations:

- How to build a container image (Cloud Native Buildpacks)
- How to deploy the application (Kubernetes YAML manifests)
- How to access the application (port forwarding)

Listing 7.6 Tilt configuration for Catalog Service (Tiltfile)

```
# Build
custom_build(
    # Name of the container image
    ref = 'catalog-service',
    # Command to build the container image
    command = './gradlew bootBuildImage --imageName $EXPECTED_REF',
    # Files to watch that trigger a new build
    deps = ['build.gradle', 'src']
)

# Deploy
k8s_yaml(['k8s/deployment.yml', 'k8s/service.yml'])

# Manage
k8s_resource('catalog-service', port_forwards=['9001'])
```

TIP If you're working on ARM64 machines (such as Apple Silicon computers), you can add the `--builder ghcr.io/thomasvitale/java-builder-arm64` argument to the `./gradlew bootBuildImage --imageName $EXPECTED_REF` command to use an experimental version of Paketo Buildpacks with ARM64 support. Be aware that it's experimental and