`polardb_catalog` database used by Catalog Service and the new `polardb_order` database used by Order Service.

Go to your `polar-deployment` repository, and create a new docker/postgresql folder. Then add a new init.sql file in the folder. Add the following code to the init.sql file; it is the initialization script that PostgreSQL should run during the startup phase.

Listing 8.2 Initializing the PostgreSQL server with two databases

```
CREATE DATABASE polardb_catalog;
CREATE DATABASE polardb_order;
```

Next, open the docker-compose.yml file and update the PostgreSQL container definition to load the initialization script. Remember to remove the value for the `POSTGRES_DB` environment variable, since we'll now delegate the database creation to the script. In the book's source code, refer to Chapter08/08-end/polar-deployment/docker to check the final result.

Listing 8.3 Initializing the PostgreSQL server from an SQL script

```
version: "3.8"
services:
  ...
  polar-postgres:
    image: "postgres:14.4"
    container_name: "polar-postgres"
    ports:
      - 5432:5432
    environment:                                    ❶
      - POSTGRES_USER=user
      - POSTGRES_PASSWORD=password
    volumes:                                        ❷
      - ./postgresql/init.sql:/docker-entrypoint-initdb.d/init.sql
```

❶ No value is defined for POSTGRES_DB anymore.

❷ Mounts the initialization SQL script to the container as a volume