```
public record OrderRequest (

  @NotBlank(message = "The book ISBN must be defined.")
  String isbn,                                                    ❶

  @NotNull(message = "The book quantity must be defined.")
  @Min(value = 1, message = "You must order at least 1 item.")
  @Max(value = 5, message = "You cannot order more than 5 items.")
  Integer quantity                                                ❷
){}
```

❶ Must not be null and must contain at least one non-whitespace character

❷ Must not be null and must contain a value from 1 to 5

In the same package, create an `OrderController` class to define the two RESTful endpoints exposed by the Order Service application. Since you defined validation constraints for the `OrderRequest` object, you also need to use the familiar `@Valid` annotation to trigger the validation when the method is called.

Listing 8.15 Defining handlers to process REST requests

```
package com.polarbookshop.orderservice.order.web;

import javax.validation.Valid;
import com.polarbookshop.orderservice.order.domain.Order;
import com.polarbookshop.orderservice.order.domain.OrderService;
import reactor.core.publisher.Flux;
import reactor.core.publisher.Mono;
import org.springframework.web.bind.annotation.*;

@RestController                                          ❶
@RequestMapping("orders")                                ❷
public class OrderController {
  private final OrderService orderService;
  public OrderController(OrderService orderService) {
    this.orderService = orderService;
  }

  @GetMapping
  public Flux<Order> getAllOrders() {                    ❸
    return orderService.getAllOrders();
  }
```