```
spring:
  cloud:
    gateway:
      routes:                                                    ❶
        - id: catalog-route                                      ❷
          uri: ${CATALOG_SERVICE_URL:http://localhost:9001}/books
          predicates:
            - Path=/books/**                                     ❸
        - id: order-route
          uri:
${ORDER_SERVICE_URL:http://localhost:9002}/orders                ❹
          predicates:
            - Path=/orders/**
```

❶ A list of route definitions

❷ The route ID

❸ The predicate is a path to match

❹ The URI value comes from an environment variable, or else from the default.

Both the routes for Catalog Service and Order Service are matched based on a `Path` predicate. All the incoming requests with a path starting with `/books` will be forwarded to Catalog Service. If the path starts with `/orders`, then Order Service will receive the request. The URIs are computed using the value from an environment variable (`CATALOG_SERVICE_URL` and `ORDER_SERVICE_URL`). If they are not defined, the default value written after the first colon (`:`) symbol will be used. It's an alternative approach compared to how we defined URLs in the previous chapter, based on custom properties; I wanted to show you both options.

The project comes with many different predicates built-in, which you can use in your route configuration to match against any aspect of an HTTP request, including `Cookie`, `Header`, `Host`, `Method`, `Path`, `Query`, and `RemoteAddr`. You can also combine them to form *AND* conditionals. In the previous example, we used the `Path` predicate. Refer to