queue durability, and replication. Furthermore, several cloud providers offer integrations with managed RabbitMQ services.

For now, you'll run RabbitMQ as a container on your local machine. First, make sure your Docker Engine is running. Then open the docker-compose.yml file located in your `polar-deployment` repository.

NOTE If you haven't followed along with the examples, you can use Chapter10/10-begin/polar-deployment/docker/docker-compose.yml from the source code accompanying the book as a starting point.

In your docker-compose.yml file, add a new service definition using the RabbitMQ official image (including the management plugin) and expose it through port `5672` (for AMQP) and `15672` (for the management console). The RabbitMQ management plugin is convenient for inspecting exchanges and queues from a browser-based UI.

Listing 10.1 Defining a container for RabbitMQ

```
version: "3.8"
services:
  ...
  polar-rabbitmq:
    image: rabbitmq:3.10-management      ❶
    container_name: polar-rabbitmq
    ports:
      - 5672:5672                        ❷
      - 15672:15672                      ❸
    volumes:                             ❹
      - ./rabbitmq/rabbitmq.conf:/etc/rabbitmq/rabbitmq.conf
```

❶ The official RabbitMQ image with the management plugin enabled

❷ The port where RabbitMQ listens for AMQP requests

❸ The port that exposes the management GUI

❹ Configuration file mounted as a volume