```
  "version": 2
}
```

And it is. Great job! When you're done testing the system, stop all the applications (Ctrl-C) and Docker containers (`docker-compose down`).

That concludes the main implementation of the business logic for the Polar Bookshop system. The next chapter will cover security for cloud native applications using Spring Security, OAuth 2.1, and OpenID Connect.

Polar Labs

Feel free to apply what you've learned in the previous chapters and prepare the Dispatcher Service application for deployment.

1. Add Spring Cloud Config Client to Dispatcher Service to make it fetch configuration data from Config Service.
2. Configure the Cloud Native Buildpacks integration, containerize the application, and define the commit stage of the deployment pipeline.
3. Write the Deployment and Service manifests for deploying Dispatcher Service to a Kubernetes cluster.
4. Configure Tilt to automate the Dispatcher Service's deployment to your local Kubernetes cluster initialized with minikube.

Then update the Docker Compose specification and the Kubernetes manifests to configure the RabbitMQ integration for Order Service.
You can refer to the Chapter10/10-end folder in the code repository accompanying the book to check on the final result (https://github.com/ThomasVitale/cloud-native-spring-in-action).
Deploy the backing services from the manifests, available in the Chapter10/10-end/polar-deployment/kubernetes/platform/development folder, with `kubectl apply -f services`.