Next, navigate to the folder where the Keycloak Admin CLI scripts are located:

```
$ cd /opt/keycloak/bin
```

As you learned earlier, the Admin CLI is protected by the username and password we defined in Docker Compose for the Keycloak container, so we need to start an authenticated session before running any other commands:

```
$ ./kcadm.sh config credentials --server http://localhost:8080 \
    --realm master --user user --password password
```

Finally, register Edge Service as an OAuth2 Client in the `PolarBookshop` realm:

```
$ ./kcadm.sh create clients -r PolarBookshop \
    -s clientId=edge-service \                          ❶
    -s enabled=true \                                   ❷
    -s publicClient=false \                             ❸
    -s secret=polar-keycloak-secret \                   ❹
    -s 'redirectUris=["http://localhost:9000",
    ➥"http://localhost:9000/login/oauth2/code/*"]'     ❺
```

❶ The OAuth2 Client identifier

❷ It must be enabled.

❸ Edge Service is a confidential client, not public.

❹ Since it’s a confidential client, it needs a secret to authenticate with Keycloak.

❺ The application URLs to which Keycloak is authorized to redirect a request after a user login or logout

The valid redirect URLs are the endpoints exposed by the OAuth2 Client application (Edge Service) where Keycloak will redirect authentication requests. Since Keycloak can include sensitive information in a redirect request, we want to limit which applications and endpoints are authorized to receive such information. As you’ll learn later, the redirect URL for