- The user is authenticated but doesn't have the `employee` role.
- The user is not authenticated.

Delete operations are only allowed to the bookshop employees, so only the first request will return a successful answer.

As part of the OAuth2 Access Token validation, Spring Security relies on the public keys provided by Keycloak to verify the JWT signature. Internally, the framework configures a `JwtDecoder` bean to decode and verify a JWT using those keys. In the context of a web slice test, we can provide a mock `JwtDecoder` bean so that Spring Security skips the interaction with Keycloak (which we'll validate later in a full integration test).

Listing 12.12 Verifying security policies at the web layer with slice tests

```
@WebMvcTest(BookController.class)
@Import(SecurityConfig.class)                                    ❶
class BookControllerMvcTests {

  @Autowired
  MockMvc mockMvc;

  @MockBean
  JwtDecoder jwtDecoder;                                         ❷

  ...

  @Test
  void whenDeleteBookWithEmployeeRoleThenShouldReturn204()
    throws Exception
  {
    var isbn = "7373731394";
    mockMvc                                                      ❸
      .perform(MockMvcRequestBuilders.delete("/books/" + isbn)
        .with(SecurityMockMvcRequestPostProcessors.jwt()
           .authorities(new SimpleGrantedAuthority("ROLE_employee"))))
      .andExpect(MockMvcResultMatchers.status().isNoContent());
  }
```