Let's set up `CatalogServiceApplicationTests` to authenticate with Keycloak as Isabelle and Bjorn so that we can obtain the Access Tokens we need to call the Catalog Service's protected endpoints. Keep in mind that Isabelle is both a customer and employee, whereas Bjorn is only a customer.

Listing 12.14 Setup for obtaining test Access Tokens

```
@SpringBootTest(webEnvironment = SpringBootTest.WebEnvironment.RANDOM_PORT)
@ActiveProfiles("integration")
@Testcontainers
class CatalogServiceApplicationTests {
  private static KeycloakToken bjornTokens;
  private static KeycloakToken isabelleTokens;
  ...

  @BeforeAll
  static void generateAccessTokens() {
    WebClient webClient = WebClient.builder()                    ❶
      .baseUrl(keycloakContainer.getAuthServerUrl()
        + "realms/PolarBookshop/protocol/openid-connect/token")
      .defaultHeader(HttpHeaders.CONTENT_TYPE,
        MediaType.APPLICATION_FORM_URLENCODED_VALUE)
      .build();

    isabelleTokens = authenticateWith(                           ❷
      "isabelle", "password", webClient);
    bjornTokens = authenticateWith(                              ❸
      "bjorn", "password", webClient);
  }

  private static KeycloakToken authenticateWith(
    String username, String password, WebClient webClient
  ) {
    return webClient
      .post()
      .body(                                                     ❹
        BodyInserters.fromFormData("grant_type", "password")
        .with("client_id", "polar-test")
        .with("username", username)
        .with("password", password)
      )
      .retrieve()
      .bodyToMono(KeycloakToken.class)
      .block();                                                  ❺
  }
```