deployment/docker/observability). Copy the observability folder over the same path in your own project.

Listing 13.3 Defining containers for Grafana, Loki, and Fluent Bit

```
version: "3.8"
services:
  ...

  grafana:
    image: grafana/grafana:9.1.2
    container_name: grafana
    depends_on:
      - loki
    ports:
      - "3000:3000"
    environment:                                                    ❶
      - GF_SECURITY_ADMIN_USER=user
      - GF_SECURITY_ADMIN_PASSWORD=password
    volumes:                                                        ❷
      - ./observability/grafana/datasource.yml:/etc/grafana/provisioning/
➥datasources/datasource.yml
      - ./observability/grafana/dashboards:/etc/grafana/provisioning/
➥dashboards
      - ./observability/grafana/grafana.ini:/etc/grafana/grafana.ini
  loki:
    image: grafana/loki:2.6.1
    container_name: loki
    depends_on:
      - fluent-bit
    ports:
      - "3100:3100"

  fluent-bit:
    image: grafana/fluent-bit-plugin-loki:2.6.1-amd64
    container_name: fluent-bit
    ports:
      - "24224:24224"
    environment:
      - LOKI_URL=http://loki:3100/loki/api/v1/push                  ❸
    volumes:                                                        ❹
      - ./observability/fluent-bit/fluent-bit.conf:/fluent-bit/etc/
➥fluent-bit.conf
```

❶ Username and password to access Grafana

❷ Volumes are used to load configuration for data sources and dashboards.

❸ Defines the Loki URL used to forward log messages