When working with Spring Boot, we can take advantage of the power of Spring profiles. Instead of updating values in the existing ConfigMap, we can add an application-staging.yml file, which we know takes precedence over application.yml when the `staging` profile is active. The final result will be a ConfigMap containing both files.

First, let's create an application-staging.yml file within the staging overlay for Catalog Service. We'll use this property file to define a different value for the `polar .greeting` property. Since we'll use the same minikube cluster from earlier as the staging environment, URLs to backing services and credentials will be the same as in the development environment. In a real-world scenario, this stage would involve more customizations.

Listing 14.13 Staging-specific configuration for Catalog Service

```
polar:
  greeting: Welcome to the book catalog from a staging
➥Kubernetes environment!
```

Next we can rely on the ConfigMap Generator provided by Kustomize to combine the application-staging.yml file (defined in the staging overlay) with the application.yml file (defined in the base `Kustomization`) within the same `catalog-config` ConfigMap. Go ahead and update the kustomization.yml file for the staging overlay as follows.

Listing 14.14 Merging property files within the same ConfigMap

```
apiVersion: kustomize.config.k8s.io/v1beta1
kind: Kustomization

resources:
  - github.com/<your_github_username>/catalog-service/k8s?ref=main

patchesStrategicMerge:
  - patch-env.yml

configMapGenerator:
```