`<your_github_username>/catalog-service:<commit-hash>`.

Now that we have a strategy, let's see how we can implement it for Catalog Service. Go to your Catalog Service project (catalog-service), and open the commit-stage.yml file within the .github/workflows folder. We previously defined a `VERSION` environment variable to hold the release candidate's unique identifier. At the moment, it's statically set to `latest`. Let's replace that with `${{ github.sha }}`, which will be dynamically resolved to the current Git commit hash by GitHub Actions. For convenience, we'll also add the `latest` tag to the newest release candidate, which is useful for local development scenarios.

Listing 15.1 Using the Git commit hash to version release candidates

```
name: Commit Stage
on: push

env:
  REGISTRY: ghcr.io
  IMAGE_NAME: polarbookshop/catalog-service
  VERSION: ${{ github.sha }}                                          ❶

build:
  name: Build and Test
  ...

package:
  name: Package and Publish
  ...
  steps:
    ...
    - name: Publish container image                                   ❶
      run: docker push \
             ${{ env.REGISTRY }}/${{ env.IMAGE_NAME }}:${{ env.VERSION }}
    - name: Publish container image (latest)                          ❷
      run: |
        docker tag \
          ${{ env.REGISTRY }}/${{ env.IMAGE_NAME }}:${{ env.VERSION }} \
          ${{ env.REGISTRY }}/${{ env.IMAGE_NAME }}:latest
        docker push ${{ env.REGISTRY }}/${{ env.IMAGE_NAME }}:latest
```