in the meantime. We are only interested in the newest one, so the others can be discarded. GitHub Actions provides a mechanism for handling this scenario via concurrency controls.

Listing 15.3 Configuring concurrency for the workflow execution

```
name: Acceptance Stage
on:
  workflow_run:
    workflows: ['Commit Stage']
    types: [completed]
    branches: main
concurrency: acceptance    ❶
```

❶ Ensures that only one workflow runs at a time

Next, you would define several jobs to run in parallel against a production-like environment, accomplishing functional and non-functional acceptance tests. For our example, we'll simply print a message, since we haven't implemented the autotests for this stage.

Listing 15.4 Running functional and non-functional acceptance tests

```
name: Acceptance Stage
on:
  workflow_run:
    workflows: ['Commit Stage']
    types: [completed]
    branches: main
concurrency: acceptance

jobs:
  functional:                                                    ❶
    name: Functional Acceptance Tests
    if: ${{ github.event.workflow_run.conclusion == 'success' }}
    runs-on: ubuntu-22.04
    steps:
      - run: echo "Running functional acceptance tests"
  performance:                                                   ❶
    name: Performance Tests
    if: ${{ github.event.workflow_run.conclusion == 'success' }}
    runs-on: ubuntu-22.04
    steps:
      - run: echo "Running performance tests"
```