First, create an application-prod.yml file within the production overlay for Catalog Service (kubernetes/applications/catalog-service/production). We'll use this property file to configure a custom greeting. We also need to instruct Spring Boot to load the Secrets as config trees, using the `spring.config.import` property. For more information on config trees, refer to chapter 14.

Listing 15.10 Production-specific configuration for Catalog Service

```
polar:
  greeting: Welcome to our book catalog from a production
➥Kubernetes environment!
spring:
  config:
    import: configtree:/workspace/secrets/*/      ❶
```

❶ Imports configuration from the path where volumes with Secrets are mounted. Make sure you include the final slash, or the import will fail.

Next, we can rely on the ConfigMap Generator provided by Kustomize to combine the application-prod.yml file (defined in the production overlay) with the application.yml file (defined in the base `Kustomization`), within the same `catalog-config` ConfigMap. Go ahead and update the kustomization.yml file for the production overlay as follows.

Listing 15.11 Merging property files within the same ConfigMap

```
apiVersion: kustomize.config.k8s.io/v1beta1
kind: Kustomization

resources:
  - github.com/<your_github_username>/catalog-service/k8s?ref=<release_sha>

patchesStrategicMerge:
  - patch-env.yml
  - patch-volumes.yml

configMapGenerator:
  - behavior: merge                  ❶
    files:
```