Now you can call Catalog Service from your local machine on port 9001, and the request will be forwarded to the Service object inside the Kubernetes cluster. Open a new Terminal window and call the root endpoint exposed by the application to verify that the `polar.greeting` value specified in the ConfigMap for the `prod` Spring profile is used instead of the default one:

```
$ http :9001/
Welcome to our book catalog from a production Kubernetes environment!
```

Congratulations! You are officially in production! When you're done, you can terminate the port-forwarding with Ctrl-C. Finally, delete the deployment by running the following command from the production overlay folder for Catalog Service:

```
$ kubectl delete -k .
```

Kubernetes provides the infrastructure for implementing different types of deployment strategies. When we update our application manifests with a new release version and apply them to the cluster, Kubernetes performs a *rolling update*. This strategy consists in incrementally updating Pod instances with new ones and guarantees zero downtime for the user. You saw that in action in the previous chapter.

By default, Kubernetes adopts the rolling update strategy, but there are other techniques that you can employ based on the standard Kubernetes resources or you can rely on a tool like Knative. For example, you might want to use *blue/green deployments*, consisting of deploying the new version of the software in a second production environment. By doing that, you can test one last time that everything runs correctly. When the environment is ready, you move the traffic from the first (*blue*) to the second (*green*) production environment.[1]