```
tasks.named('bootBuildImage') {
  builder = 'paketobuildpacks/builder:tiny'      ❶
  environment = ['BP_NATIVE_IMAGE': 'true']      ❷
  imageName = "${project.name}"

  docker {
   publishRegistry {
     username = project.findProperty("registryUsername")
     password = project.findProperty("registryToken")
     url = project.findProperty("registryUrl")
   }
  }
}
```

❶ Uses the “tiny” version of Paketo Buildpacks to minimize the container image size

❷ Enables GraalVM support and produces a containerized native image

NOTE As you probably noticed when running the native image compilation process on your machine, it takes not only time but also more computational resources than usual. When using Buildpacks, make sure you have at least 16 GB of RAM on your computer. If you use Docker Desktop, configure the Docker virtual machine with at least 8 GB of RAM. On Windows, it’s recommended that you use Docker Desktop on WSL2 rather than Hyper-V. For more recommendations about the setup, refer to the Spring Native documentation (https://docs.spring.io/spring-native/docs/current/reference/htmlsingle).

The command to use Buildpacks and produce a containerized native image is the same that you’d use for JVM images. Open a Terminal window, navigate to your Quote Service project (quote-service), and run the following command:

```
$ ./gradlew bootBuildImage
```

When it’s done, try running the resulting container image:

```
$ docker run --rm -p 9101:9101 quote-service
```

The startup time should again be less than 100 ms. Go ahead and send a few requests to test whether the application is working correctly: