- *Knative Serving* is for running serverless workloads on Kubernetes. It takes care of autoscaling, networking, revisions, and deployment strategies while letting engineers focus on the application business logic.
- *Knative Eventing* provides management for integrating applications with event sources and sinks based on the CloudEvents specification, abstracting backends like RabbitMQ or Kafka.

Our focus will be on using Knative Serving to run serverless workloads while avoiding vendor lock-in.

NOTE Originally, Knative consisted of a third component called "Build" that subsequently became a standalone product, renamed Tekton (https://tekton.dev) and donated to the Continuous Delivery Foundation (https://cd.foundation). Tekton is a Kubernetes-native framework for building deployment pipelines that support continuous delivery. For example, you could use Tekton instead of GitHub Actions.

This section will show you how to set up a local development environment comprising both Kubernetes and Knative. Then I'll introduce Knative manifests, which you can use to declare the desired state for serverless applications, and I'll show you how to apply them to a Kubernetes cluster.

16.3.1 Setting up a local Knative platform

Since Knative runs on top of Kubernetes, we first need a cluster. Let's create one with minikube following the same approach we've used throughout the book. Open a Terminal window and run the following command:

```
$ minikube start --profile knative
```

Next, we can install Knative. For simplicity, I have collected the necessary commands in a script that you'll find in the source code repository