Definitions (CRDs). That is the strategy used by many tools built on top of Kubernetes, including Knative.

One of the benefits of using Knative is a better developer experience and the possibility to declare the desired state for our applications in a more straightforward and less verbose way. Rather than dealing with Deployments, Services, and Ingresses, we can work with a single type of resource: the Knative Service.

NOTE Throughout the book, I talked about applications as *services*. Knative offers a way to model an application in a single resource declaration: the Knative Service. At first, the naming might not be very clear, since there is already a Kubernetes built-in Service type. In reality, the Knative choice is very intuitive because it maps one-to-one the architectural concept with the deployment concept.

Let's see what Knative Services look like. Open your Quote Function project (quote-function), and create a new "knative" folder. Then, define a new kservice.yml file inside to declare the desired state of the Knative Service for Quote Function. Remember to replace `<your_github_username>` with your GitHub username in lowercase.

Listing 16.13 Knative Service manifest for Quote Function

```
apiVersion: serving.knative.dev/v1                    ❶
kind: Service                                         ❷
metadata:
  name: quote-function                                ❸
spec:
  template:
    spec:
      containers:
        - name: quote-function                        ❹
          image:                                      ❺
➥ghcr.io/<your_github_username>/quote-function
          ports:
            - containerPort: 9102                     ❻
          resources:                                  ❼
            requests:
              cpu: '0.1'
              memory: '128Mi'
```