Listing 8.1 shows the relevant snippets (focusing on the wiring and configuration of our microservices app) of the Docker Compose file.

Listing 8.1 The Docker Compose configuration for the Jaeger setup

```
frontend:                                  # Frontend service of our microservice app,
    environment:                           # which calls service-a and service-b
    - "DOWNSTREAM0=http://service-a:8766"
    - "DOWNSTREAM1=http://service-b:8767"
    - "DOWNSTREAM2=https://opentelemetry.io/img/logos/opentelemetry.png"
  service-a:                               # The service-a that calls out
    environment:                           # to static web content
    - "HO11Y_PORT=8766"
    - "DOWNSTREAM0=https://mhausenblas.info/"
    - "DOWNSTREAM1=https://otel.help/"
  service-b:                               # The service-b that calls
    environment:                           # service-b0 and service-b1
    - "HO11Y_PORT=8767"
    - "DOWNSTREAM0=http://service-b0:8768"
    - "DOWNSTREAM1=http://service-b1:8769"
  service-b0:                              # The service-b0 that can be throttled
    environment:                           # and then returns HTTP status code 429
    - "HO11Y_PORT=8768"
    - "DOWNSTREAM0=https://example.net/"
    # - "HO11Y_CUTOFF_TPS=1"
  service-b1:                              # The serviceb1 that can simulate failure by returning
    - "HO11Y_PORT=8769"                    # HTTP 4xx/5xx status codes half of the time
    - "DOWNSTREAM0=https://www.w3.org/TR/trace-context/"
    - "DOWNSTREAM1=https://example.org/"
    # - "HO11Y_INJECT_FAILURE=enabled"
```

The OpenTelemetry collector config shown in the next listing is essentially the same that we used in chapter 6, with a single trace pipeline to ingest spans into Jaeger.

Listing 8.2 Collector config for collecting traces in OTLP and ingesting into Jaeger

```
receivers:
  otlp:
    protocols:
      grpc:
        endpoint: 0.0.0.0:4317
processors:
  batch:                                   # The batch size is intentionally
    timeout: 1s                            # small for demonstration purposes.
    send_batch_size: 10
exporters:
  jaeger:
    endpoint: jaeger:14250
    tls:
      insecure: true
service:
  pipelines:
```