ch09/parca, so change to that directory. First off, to see profiles from the OpenTelemetry collector, you need to have the pprof extension (http://mng.bz/6D6e) configured in the collector (see the otel-config.yaml file below for details). So let's bring up the Docker Compose stack in the usual form:

```
docker-compose -f docker-compose.yaml up
```

The following listing shows the snippets of the Compose file pertinent to our conversation.

Listing 9.1 The relevant snippets of the Docker Compose configuration for the Parca setup

```
otel-collector:
    image: otel/opentelemetry-collector-contrib:0.68.0
    command: [
      "--config=/conf/otel-collector-config.yaml"
    ]
    volumes:
    - ./otel-config.yaml:/conf/otel-collector-config.yaml
    ports:
    - "4317:4317"
    - "1777:1777"

  parca:
    image: ghcr.io/parca-dev/parca:v0.15.0
    command: /parca --config-path=/opt/parca.yaml
    ports:
    - "7070:7070"
    volumes:
    - "./parca.yaml:/opt/parca.yaml"
```

We expose the pprof extension on this port in the OpenTelemetry collector.

Parca, as the server, providing service discovery and UI.

The Parca configuration file

The OpenTelemetry collector config in otel-config.yaml shown in the following listing configures a simple trace pipeline to send traces to stdout of the collector via the logging exporter.

Listing 9.2 The OpenTelemetry collector configuration for producing profiles

```
receivers:
  otlp:
    protocols:
      grpc:
        endpoint: 0.0.0.0:4317

exporters:
  logging:
    loglevel: debug

extensions:
  pprof:
    endpoint: "otel-collector:1777"
```

The pprof extension for collector self-telemetry profile generation