```
                                    public{                                 ❺
      address fromAirline=msg.sender;
      uint amt = msg.value;
      balanceDetails[toAirline].escrow = balanceDetails[toAirline].escrow
                                                 + amt;
      balanceDetails[fromAirline].escrow =
              balanceDetails[fromAirline].escrow - amt;

     // amt subtracted from msg.sender and given to toAirline
      toAirline.transfer(amt);                                              ❼
  }}
```

❶ Airline data structures

❷ Airline account payments and membership mapping

❸ Modifier for onlyChairperson rule

❹ Modifier for onlyMember rule

❺ Functions of the contract

❻ Usage of msg.sender and msg.value for a payable function

❼ Smart contract account transferring amount to an external account

Let’s take a look at the new Solidity data types introduced by this smart contract. These data types include

- `address` to refer to the identity of the chairperson.
- `struct` to collectively define the data of the airlines, including the escrow or the deposit.
- `mapping` to map account addresses (identities) of members to their details. (A mapping is like a hash table.)
- `modifier` definitions for `memberOnly` and `chairpersonOnly`. (You’ll learn about these definitions in chapter 3.)

These data types are followed by the function definitions: `constructor()`, `register()`, `request()`, `response()`, `settlePayment()`, and `unregister()`. It’s important to