Account address or identity	Airline
0xca35b7d915458ef540ade6068dfe2f44e8fa733c	ASK consortium chairperson
0x14723a09acff6d2a60dcdf7aa4aff308fddc160c	`fromAirline` (for testing airline A)
0x4b0897b0513fdc7c541b6d9d7e929c4e5364d2db	`toAirline` (for testing airline B)
0x583031d1113ad414f02576bd6afabfb302140225	Another airline
0xdD870fA1b7C4700F2BD7f44238821C26f7392148	Yet another airline

You need only the first three account numbers for testing purposes. Copy them from the IDE, and store them in a notepad application so that it is easy for you to copy and paste them in the interface.

TEST PLAN DESCRIPTION

> **NOTE** I've described a test plan followed by actual instructions. If you're a beginner, review both, but if you're an advanced developer, you may choose to do either.

Here's a simple test plan to verify the execution of your functions in the IDE:

- `constructor()` *function* --The constructor is executed upon deployment of the contract. Set the Value field in the blockchain simulator panel at the top left to 50 ether, as shown in figure 2.14. The selected account is that of the chairperson. The meaning of this initialization is that the chairperson deposits a value of 50 ether. Now click the Deploy button. You'll see the account balance go down by this amount after the constructor is executed.