accounts available in the Remix IDE. Recall from the problem statement (section 3.2) and use case diagram (figure 3.3) that the chairperson is also a voter and that the chairperson's vote is weighted twice as heavily as that of a regular voter.

Table 3.1 Accounts and their roles

Account addresses	Roles
0xca35b7d915458ef540ade6068dfe2f44e8fa733c	Chairperson and voter (weight =2)
0x14723a09acff6d2a60dcdf7aa4aff308fddc160c	Voter (weight =1)
0x4b0897b0513fdc7c541b6d9d7e929c4e5364d2d	Voter (weight =1)
0x583031d1113ad414f02576bd6afabfb302140225	Voter (weight =1)
0xdD870fA1b7C4700F2BD7f44238821C26f7392148	Yet another voter

> **NOTE** The five accounts in Table 3.1 used to be the only five accounts in the previous version of Remix IDE (2019). The newer version of Remix IDE (2020) has ten additional test accounts that are random, which means that these accounts are different every time you reload. I've chosen to use the permanent five accounts at the bottom of the Account drop-down list of the Remix IDE. Be aware of such changes in the future, and be ready to adapt.

A robust testing process includes two different types of testing:

- *Positive tests* --When given a valid set of data inputs, make sure that the smart contract performs correctly and as expected
- *Negative tests* --When given invalid data inputs, make sure that the smart contract catches errors during verification and validation and that functions revert.

3.3.1 Positive tests

Let's begin testing with the positive tests. In the Remix IDE, follow these steps: