❹ placeBid() is an internal function.

❺ withdraw() is invoked by losers.

❻ auctionEnd() function is invoked in the Done phase.

Now it’s time to test the blind auction smart contract. You can do that by using the Remix IDE or the Truffle console; you can even make it into a full-fledged end-to-end Dapp after developing the web front end. We’ll implement an improved version of the blind auction smart contract and a full Dapp in chapter 6. In this chapter, let’s focus on learning the secure hashing by exploring the application through the Remix IDE.

5.4.4 Testing the BlindAuction contract

You’ll need a test plan (as discussed in chapter 3) to explore the operation of the smart contract code for the blind auction. Let’s assume the following as preparation before testing:

- You need at least three participants: the beneficiary and at least two bidders. Let’s choose the first three accounts of the Remix IDE: account[0], account[1], and account[2], with addresses that begin with 0xca3..., 0x147..., and 0x4b0..., respectively. You have to choose account[0], account[1], and account[2] from the drop-down list in the Remix simulated environment.
- account[0] will be the beneficiary, the one that deploys the smart contract, and the only one that can change the phase of the auction. For account[0], I’ve used the address 0xca3....
- account[1] and account[2] will be the two bidders for testing purposes. I used 0x147.. for account[1] and 0x4B0.. for account[2].
- account[1] will place a blind bid of 20 with a deposit (value) of 50 wei, and account[2] will place a blind bid of 30 with a deposit of 50 wei.