TESTING THE BLIND AUCTION USING THE WEB UI

Restart your browser, and make sure that MetaMask has connected to Ganache on the localhost. If MetaMask is already installed as a plugin and connected to the Ganache chain, make sure that Account 1, Account 2, and Account 3 are visible. Be sure to reset the nonce of all three accounts before you begin testing. The nonce maintains a running count of the Txs issued from an account; it's persistent and may be stored from your earlier test runs, so it's good practice to clear it before you begin testing a new project.

To reset nonce, with Account 1 selected, click the account icon (the ball to the right of the MetaMask icon); select Settings, Advanced option; and scroll down and click Reset Account to reset the nonce of that account. Repeat this process for the other two accounts. You need only these three accounts for minimal testing. In this test plan, Account 1 is the beneficiary or auctioneer, and the other two accounts are the bidders.

For the first test, click the MetaMask icon, and choose Account 1 from the list that opens. Then click Advance Phase at the bottom of the web UI. Keep clicking the button until you complete a full cycle from `Init` back to `Init`. You'll see notifications for the various phases, including `Bidding` and `Reveal`, in the top-left corner of the UI, as shown in figure 6.7. The notifications represent the logs in the Tx receipts that are recorded in the block. In section 6.2.4, you'll see code snippets in app.js that access these event logs to notify users of the phase changes.