their parameters. These parameters get assigned to smart contract variables, which in turn enables them to be recorded in the state tree. Also note the use of the Solidity `mapping` feature, which allows you to build on-chain data for the status of membership and other operations of the ASK system.

Listing 6.2 Updated Airlines smart contract (Airlines.sol)

```
pragma solidity >=0.4.22 <=0.6.0;

    contract Airlines  {

    address chairperson;

    struct reqStruc{                                                    ❶
        uint reqID;
        uint fID;
        uint numSeats;
        uint passengerID;
        address toAirline;
    }

   struct respStruc{                                                    ❷
        uint reqID;
        bool status;
        address fromAirline;
    }

    mapping (address=>uint) public escrow;                              ❸❹
    mapping (address=>uint) membership;                                 ❸❹
    mapping (address=>reqStruc) reqs;                                   ❸❹
    mapping (address=>respStruc) reps;                                  ❸❹
    mapping (address=>uint) settledReqID;                               ❸❹

    //modifier or rules
    modifier onlyChairperson {
        require(msg.sender==chairperson);
        _;
    }
    modifier onlyMember {
        require(membership[msg.sender]==1);
        _;
    }

    constructor () public payable  {

        chairperson=msg.sender;
        membership[msg.sender] = 1; // automatically registered          ❺
        escrow[msg.sender] = msg.value;
    }
```