- Organizer opens a channel. A smart contract is deployed and initialized with the accounts of the two participants: the organizer and the worker. The organizer deposits an escrow for payments. A channel is created for every worker.
- Micropayments replace checks.
- The organizer pays for micropayments in wei (for example, 1,000 wei for one bin), sending signed messages off-chain.
- The micropayments sent are monotonically increasing in value, the latest one holding the cumulative payment until that point.
- A worker claims payment by sending the most recent message that the organizer sent to collect payment and then closes the channel by destructing (via a self-destruct function) the smart contract.

As you can see, the blockchain solution is ideally suited to addressing the issues discussed in table 7.1.

> **NOTE** If the bins collected are 3, 1, and 2, for example, the micropayments are for 3, 4 (3+1), and 6 (3+1+2)--the cumulative values.

After the worker claims the one single cumulative payment, the contract is destructed or undeployed, thus addressing the cost of numerous small checks as well as fraudulent double spending (a technical term for repeat spending of a digital check) of digital payments. A micropayment is like a cash payment for a one-time job. You don’t have to establish a formal financial relationship with the vendor, such as creating and maintaining an account, so there are no cost overheads. Note that there are no paper checks in the MPC application. Therefore, the application provides a safe, secure mechanism for online digital micropayments to decentralized participants.